

# Technical Datasheet

		EN ISO 13485 certified
<b>Article - No:</b>	<b>09-509-5000</b>	<b>Revision: 1</b>
<b>Remarks</b>		<b>single use only</b>

## Specification

<b>Product</b>	Test tube PP with fitted screw cap PE, 12ml, Ø16x100 mm, with wooden applicator with cotton ti tube transparent, cap blue, graduated, sterile R
<b>Dimensions</b>	outer diameter: 16,60 mm (+/- 0,2 mm)
	outer diameter (incl. cap): 19,60 mm (+/- 0,2 mm)
	length (cap and tube): 102,60 mm (+/- 0,2 mm)
	height cap : 14,40 mm (+/- 0,2 mm)
	cotton swab:
	diameter: 2,20 mm (+/- 0,2 mm)
	length: 85,00 mm (+/- 0,2 mm)
	diameter tip: 5,00 mm (+/- 0,2 mm)
<b>Colour</b>	tube transparent, cap blue
<b>Graduation</b>	grad.
<b>Nominal Capacity</b>	12ml
<b>Material Characteristics</b>	tube: polypropylene (PP)
	plug: polyethylene (PE)
<b>Temperature range</b>	-20°C - 60°C
<b>Product Characteristics</b>	biol. inert
	physiol. harmless
	no heavy metals acc. to EC/94/62
	Food contact: raw material in compl. with reg. EC 1935/2004
<b>Purity Grade</b>	do not contain any pyrogens
<b>Sterilisation Process</b>	radiation sterilization SAL 10-6
<b>Shelf - Life</b>	60 months at controlled storage conditions
<b>Packaging</b>	pcs per bag: 100
	pcs per carton: 1.000
	pcs per pallet: 24.000
<b>Storage</b>	dry condition: 40%-60% rel. humidity

# Technical Datasheet

Date: 22.06.20

Page 2 of 2

	bags / cases orig. closed
	storage temp. +10°C to max. +30°C
	pal. not stackable
<b>Approved by nerbe plus quality department</b>	